

## SUBJECT INDEX\*

- 2-*t*-butylbenzothiazole sulfenamide, mechanism of accelerating action in sulfur vulcanized IR (abs-S98#12) (4) 822
- 6-QDI, multifunctional chemical for the rubber industry (abs-F97#109) (1) 149
- Accelerating, sulfur vulcanization of IR, with 2-*t*-butylbenzothiazole sulfenamide (abs-S98#12) (4) 822
- Acid rain, effect on rubber compounds containing antiozonants (abs-F97#110) (1) 150
- Adhesion, between dissimilar elastomers, promoted using maleinized polybutadiene resins (abs-F97#20) (1) 124
- Adhesion, between polymers, contact-mechanics-based studies (rev) (3) 407
- Adhesion, of NR to steel, use of plasma polymerized primers (abs-F97#49) (1) 133
- Adhesive, textile-to-rubber, from shorea robusta resin (abs-F97#7) (1) 120
- Adhesives, aqueous, application characteristics (abs-F97#23) (1) 125
- Aging, long term, of polychloroprene compounds (abs-F97#54) (1) 135
- Aging, of PDMS elastomers prepared from aqueous emulsions
- Alkyl tetrahydrofurfuryl ether modifiers, for anionic polymerization of isoprene (1) 62
- Antioxidants, blend of special triazine and octylated diphenyl amine, for black sidewall tires (abs-F97#64) (1) 137
- Antioxidants, effect on long-term aging of EPDM electrical insulations (abs-S98#27) (4) 826
- Antiozonants, effect of acid rain on rubber compounds containing (abs-F97#110) (1) 150
- Antiozonants, *p*-phenylenediamine-type, protection mechanisms of (4) 722
- Aramid fibers, for mechanical rubber goods (abs-F97#6) (1) 120
- Aramid fibers, metal clad, for use with wire and cable (abs-S98#37) (4) 828
- Asphalt pavements, using pyrolyzed carbon black from scrap tires (abs-F97#115A) (1) 151
- Atomic force microscopy, for tracking morphological change in elastomers for transmission seals (abs-F97#67) (1) 138
- Automotive applications, of specialty elastomers (rev) (3) 440
- Automotive wire and cable, recent advances (abs-S98#32) (4) 827
- BCI-MX [1,3-bis-(citraconimidomethyl)benzene], for reversion resistance of diene rubbers (abs-F97#107) (1) 149
- BIMS (terpolymer of isobutylene, *p*-methylstyrene, *p*-bromomethylstyrene), backbone of graft copolymers (4) 803
- BIMS [poly(isobutylene-co-4-methylenestyrene)] elastomer cure with HTR, studied by XANES (abs-S98#10) (4) 822
- BIMS polymers, for non-stain tire sidewalls (abs-F97#66) (1) 138
- BR, oxidation, studied by DSC (abs-S98#11) (4) 822
- Baby bottle nipples, detecting volatile *N*-nitrosamines in (abs-F97#130) (1) 155
- Batch mixing, overview of variables affecting (abs-F97#87) (1) 143
- Belting, power transmission, performance and failure studies (abs-F97#47) (1) 133
- Bending and transverse compression, effect on fatigue in *para*-aramid knitted hose (abs-F97#50) (1) 134
- Bis(3-triethoxysilylpropyl)tetrasulfide, effect on silica reinforcement of SBR (2) 289
- Bis-maleimides and bis-citraconimides, crosslinking reaction in squalene and in NR (5) 1073
- Bisphenol AF/osmium cure system, for fluoroelastomer, for storage stability (abs-F97#26) (1) 126

\*Prepared by Lois W. Brock.

- Black-filled NR, tensile and tear behavior of anisotropic double networks (5) 846
- Black-filled rubber, chain end distributions and crosslink characteristics (5) 975
- Blends, of BR, NR, and brominated poly(isobutylene-co-paramethylstyrene), covulcanization (abs-F97#91) (1) 144
- Blends, of NR and BR, effect of cure temperature and time on crosslink density distribution (abs-F97#94) (1) 145
- Blends, of NR and HDPE, microscopy of unvulcanized (5) 966
- Blends, of NR and SBR, crystallization studies of (5) 837
- Blends, of NR and SBR, with block copolymers as compatibilizers, morphology and mechanical properties (abs-S98#61) (4) 835
- Blends, of NR and cardinol-formaldehyde resins, for improved mechanical and thermal properties (abs-S98#58) (4) 834
- Blends, of NR/BR, crosslink density distribution, effect of cure temperature and time (5) 958
- Blends, of SBR with ultrasonically devulcanized silicone rubber, surface behavior (abs-F97#113) (1) 150
- Blends, of brominated isobutylene *p*-methylstyrene copolymer and diene elastomers, cracking (abs-S98#24) (4) 825
- Blends, of devulcanized ground tire rubber and PP (abs-F97#114) (1) 151
- Blends, of elastomers, inferring physical properties from microscopic image analysis of (abs-S98#23) (4) 825
- Block copolymers, as compatibilizers for blends of NR/SBR (abs-S98#61) (4) 835
- Blowing agents, for sponge rubber, balancing cure to control cell density and structure (abs-S98#53) (4) 833
- Book Review: "Understanding Plastics Packaging Technology," by Susan E. M. Selke (4) G53
- Book review: "Commercial polymer blends," by L. A. Utracki (3) G42
- Brominated isobutylene-co-*para*-methylstyrene, ozone resistant, for black sidewalls (rev) (3) 590
- Cable insulation, moisture cross-linkable (abs-S98#28) (4) 826
- Cable jackets, of flame retardant water-cured polyethylene (abs-S98#31) (4) 827
- Cable, with polyolefin or EPDM elastomers crosslinked with organic peroxide (abs-S98#3) (4) 820
- Calendering, mechanical and process control technologies (abs-F97#102) (1) 148
- Calix[8]arene core, for star polymer with poly(styrene-*b*-isobutylene) arms, properties of (abs-F97#18) (1) 123
- Calix[8]arene core, for star-block copolymer with 8 poly(styrene-*b*-isobutylene) arms (4) 708
- Carbon black agglomerates, in PDMS or PBD, dispersion kinetics (1) 1
- Carbon black aggregates, related to failure strain of rubber in mixing (abs-F97#59) (1) 136
- Carbon black blends, performance difference in industrial applications compared to single black (abs-S98#25) (4) 825
- Carbon black dispersion, measured by reflectometry (1) 17
- Carbon black filled NR vulcanizates, longitudinal cracking during stress (2) 157
- Carbon black filled NR, longitudinal cracking during chemical relaxation (abs-F97#53) (1) 134
- Carbon black networks, fractal nature and dynamic behavior of elastomers at low strain amplitudes (abs-S98#56) (4) 833
- Carbon black, compatibility with EPDM extrusion compounds (abs-F97#43) (1) 131
- Carbon black, dispersion in rubber, filler-filler and filler-polymer interactions related to (abs-S98#57) (4) 833
- Carbon black, effect of heating and cooling rates on structure (1) 26
- Carbon black, effect on ultrasound devulcanization of sulfur cured SBR (abs-F97#99) (1) 146
- Carbon black, morphology and microdispersion of aggregates in vulcanizates (abs-S98#46) (4) 831
- Carbon black, parallelism between mechanical and dielectric behavior (abs-S98#47) (4) 831
- Carbon black, particle size distribution determined by mercury porosimetry (5) 988
- Carbon black, structure and shape studied by small angle neutron scattering (abs-S98#41) (4) 829
- Carbon black, structure and surface studied by scanning probe microscopy and SAXS (abs-S98#40) (4) 829
- Carbon black, study of particles under high pressure Raman spectra (abs-S98#39) (4) 829
- Carbon black, surface characterization by ToF-SIMS and XPS (abs-S98#38) (4) 828
- Carbon black-filled NR, tensile and tear behavior of anisotropic double networks (abs-S98#60A) (4) 834
- Carbon black-filled rubbers, hysteresis in tin-end modified polymers (4) 637

- Carbon-silica dual phase filler, estimating functional groups on surface of (5) 1015
- Carbon-silica dual phase filler, surface chemistry study of reactive functional groups (abs-F97#73) (1) 139
- Carbon-silica dual phase fillers, ESCA and IR characterization of (abs-F97#71) (1) 139
- Carbon-silica dual phase filler, studies showing silica incorporated into matrix (abs-S98#9) (4) 822
- Carbon-silica dual phase filler, studying by ESCA and IR (5) 998
- Carbon-silica filler, time-temperature superposition of dynamic properties of vulcanizates (abs-S98#20) (4) 824
- Cardinol-formaldehyde resins, blended with NR, for improved mechanical and thermal properties (abs-S98#58) (4) 834
- Carrier Gum, specially formulated for recycling of fluoroelastomer scrap (abs-F97#115) (1) 151
- Catalysts, constrained geometry, for making EPDM (abs-F97#45) (1) 132
- Cavity filling, during injection molding, experimental studies with NR (abs-F97#78) (1) 141
- Cellular rubber, deformation studied in biaxial mode by new model in FEM (abs-S98#49) (4) 831
- Chain end distributions and crosslink characteristics, in black-filled rubber (5) 975
- Chain scission, in black-filled rubber during mixing (5) 975
- Chain-folded lamellar crystal grown from dilute solution of NR, finding stem length (2) 277
- Chemical crosslink density and chain entanglement, of EPDM studied with low resolution  $^1\text{H}$  NMR (1) 105
- Cluster-cluster aggregation model, for explaining reinforcing action of carbon black in elastomers (abs-S98#56) (4) 833
- Composites, of reinforced rubber matrix, testing methodology for (abs-F97#46) (1) 132
- Compounding, with computer-aided information retrieval (abs-F97#5) (1) 120
- Compressibility, of porous bonded blocks (abs-F97#55) (1) 135
- Compression grooving, as indicator of over-deflected operating conditions in tires (abs-F97#51) (1) 134
- Compression set, of EPDM made by constrained geometry catalyst and sulfur vulcanized (abs-S98#52) (4) 832
- Compression set, of HNBR (abs-F97#125) (1) 154
- Computational chemistry, using quantum mechanics and computer programs (abs-F97#56) (1) 135
- Computer-aided design, using on-line documentation (abs-F97#5) (1) 120
- Computer-controlled evaluation, of traction and wear properties of tire tread (abs-F97#119) (1) 152
- Contact analysis, large deformation, by Reproducing Kernel Particle Method (2) 168
- Contact mechanics, as applied to molecular level adhesion between polymers (rev) (3) 407
- Cord-rubber composites, effect of sample geometry on mechanical characteristics (abs-F97#10) (1) 121
- Cord-rubber composites, in aircraft tires, minimum stress effect in determining fatigue (5) 889
- Cord-rubber composites, minimum stress effect in fatigue (abs-F97#36) (1) 129
- Cord-rubber composites, strain-based failure criteria in assessing fatigue (5) 866
- Cord-rubber composites, studying through mathematical modeling (abs-F97#9) (1) 121
- Core-first strategy, in forming star block copolymers with poly(styrene-*b*-isobutylene) (4) 708
- Coupling agents, aqueous, based on poly(acrylic acid) and poly(vinylamine), for EPDM adhesion (abs-S98#70) (4) 836
- Crack growth resistance, to improve appearance of tire sidewalls (abs-F97#65) (1) 138
- Crack growth, determined by torsion test method (1) 84
- Crack growth, in twisted rubber disks, fracture energy calculation in (1) 76
- Cracking, longitudinal, in carbon black filled NR vulcanizate during chemical relaxation (abs-F97#53) (1) 134
- Cracking, longitudinal, in carbon black filled NR vulcanizate during chemical stress relaxation (2) 157
- Crosslink density distribution, in NR/BR blends, effect of cure temperature and time (5) 958
- Crosslink density distribution, in NR/BR blends, effect of cure temperature and time (abs-F97#94) (1) 145
- Crosslinking mechanism, of PDMS elastomers prepared from aqueous emulsions (5) 906
- Crosslinking reaction, of bis-maleimides and bis-citraconimides in squalene and NR (5) 1073
- Crosslinking reaction, of elastomers using peroxides (abs-S98#6) (4) 821
- Crosslinking, of HNBR, by sulfur or by peroxide (abs-S98#13) (4) 823
- Crosslinking, of polymers with organic peroxides (abs-S98#2) (4) 820
- Crosslinking, of polymers, with peroxides (abs-S98#1) (4) 820
- Cryogenic fine grinding, of scrap tires (abs-F97#111) (1) 150

- Crystal growth, of *cis*-polyisoprene, ozonolysis/GPC measurement of (2) 277
- Crystallization and strength, of NR and synthetic *cis*-1,4-polyisoprene (4) 668
- Crystallization, of *cis*- and *trans*-polyisoprene dispersed in SBR (5) 837
- Cure temperature and time, effect on crosslink density of NR/NR blends (abs-F97#94) (1) 145
- Curing, differential, of isobutylene-based elastomers, studied by solid state NMR (abs-F97#70) (1) 139
- DSC (differential scanning calorimetry), for studying oxidation of elastomers (abs-S98#11) (4) 822
- Damage-initiation and fatigue failure, in angle-ply cord-rubber composites (5) 889
- Data Collection Software, for reducing duration of IRHD hardness testing (abs-F97#4) (1) 119
- Deformation data analysis, of bias and radial tires (abs-F97#48) (1) 133
- Deformations, involving rotations of principal stretch directions, in vinyl elastomers (4) 730
- Deproteinized NR latex, for producing low molecular weight NR latex by oxidative degradation (4) 795
- Designed experiments, for rubber-metal bonding (abs-F97#25) (1) 125
- Devulcanization, continuous ultrasonic, of unfilled silicone rubber (abs-F97#96) (1) 145
- Devulcanization, ultrasonic, of SBR, modeling based on cavitation and percolation theories (2) 168
- Devulcanized recycle, for reincorporation into parent compound (abs-F97#97) (1) 146
- Diffusion, of solvents in rubber, mathematical model of (2) 285
- Dispersion kinetics, of carbon black agglomerates in PDMS or PBD (1) 1
- Dispersion, of carbon black on TEM grids for morphological characterization (abs-S98#46) (4) 831
- Distributive mixing, in variable intermeshing clearance mixers (4) 690
- Distributive mixing, in variable intermeshing clearance mixers, simulation and experiments (abs-F97#116) (1) 151
- Dithiophosphate vulcanization system, for improved reversion resistance in thick-section NR (abs-F97#106) (1) 148
- Donnet, Jean-Baptiste, Charles Goodyear Medalist, 1998, biog. (3) G39
- Double-peel adhesion test for rubber/metal bond (abs-F97#24) (1) 125
- Durable bonds, kinetics of formation (abs-F97#22) (1) 124
- ECLIPSE Laboratory Information Management System, for compounding in the 21st century (abs-F97#5) (1) 120
- EPDM compounds, branched, for modifying high flow TPOs to attain better impact resistance (abs-F97#15) (1) 122
- EPDM vulcanizates, density of crosslinks and chain entanglement studied with solid state  $^1\text{H}$  NMR (1) 105
- EPDM, adhesion to metal using water-soluble polymer coupling agents (abs-S98#70) (4) 836
- EPDM, compatibility with carbon black in extrusion compounds (abs-F97#43) (1) 131
- EPDM, complex branched, for modifying high flow TPOs to attain better impact resistance (4) 778
- EPDM, for engine mounts, laboratory testing of relevant properties (abs-F97#42) (1) 131
- EPDM, for wire and cable insulation (abs-F97#41) (1) 131
- EPDM, in electrical insulation, effect of antioxidants on long-term heat aging (abs-S98#27) (4) 826
- EPDM, in electrical insulations, viscoelastic and electrical properties (abs-S98#35) (4) 828
- EPDM, influence of molecular structure on viscoelastic and solid state behavior (abs-F97#44) (1) 132
- EPDM, optimum characteristics for continuously-vulcanized sponge (abs-S98#50) (4) 832
- EPDM, produced by constrained geometry catalyst technology, effects of plasticizers and fillers (abs-F97#45) (1) 132
- EPDM, properties of compound using re-utilized factory scrap (abs-F97#98) (1) 146
- EPDM, relation of cure time to level of nitrosamine formation (4) 766
- EPDM, sequence distribution studied by NMR to explain influence on thermal properties (abs-F97#40) (1) 130
- EPDM, sulfur cure system via constrained geometry catalyst technology (abs-S98#52) (4) 832
- EPDM, understanding extrusion behavior (abs-F97#61) (1) 136
- EPDM, using vinyl norbornene as diene, for wire and cable (abs-S98#29) (4) 827
- ESCA and infrared characterization, of carbon-silica dual phase fillers (abs-F97#71) (1) 139
- ESCA characterization, of carbon-silica dual phase filler (5) 998
- Elastomer amorphous liquids, studied in modeling elastomers (rev) (3) 342
- Elastomeric matrix composites, of polyurethane with high fiber content, viscoelasticity (5) 104
- Electrical properties, wet, with improved thermoplastic vulcanizates (abs-S98#32) (4) 827

- Engine mounts, of EPDM and HNBR, laboratory study of polymers (abs-F97#42) (1) 131
- Epichlorohydrin elastomers, for automotive applications (rev) (3) 440
- Equation, closed form, two-dimensional constitutive, for laminated elastomer composites (abs-F97#12) (1) 121
- Ethylene-propylene-dienes, ozone-resistant, for black sidewalls (rev) (3) 590
- Extruder design press, parameter settings for injection molding of rubber (abs-F97#76) (1) 140
- Extrusion behavior, of EPDM, influence of extruder screw speed and other parameters (abs-F97#61) (1) 136
- Extrusion, of rubber, studied with consideration of rheology and process modelling (abs-F97#75) (1) 140
- Extrusion, state-of-the-art, for tire components (abs-F97#104) (1) 148
- Extrusions, line laser scanning of (abs-F97#1) (1) 119
- Failure mode, importance in rubber-metal bond studies (abs-F97#25) (1) 125
- Fatigue crack growth, in wire reinforced rubber, effect of material and loading (abs-F97#35) (1) 128
- Fatigue endurance, of reinforced rubber composites, testing methodology for (abs-F97#46) (1) 132
- Fatigue, in cord-rubber composites, minimum stress effect (abs-F97#36) (1) 129
- Fatigue, of cord-rubber composites, minimum stress effects (5) 889
- Fatigue, of cord-rubber composites, strain-based failure criteria for (5) 866
- Fatty acids, effect on crystallization of NR (1) 70
- Filler dispersion, controlling for optimum mixing performance (abs-F97#102) (1) 147
- Fillers, mineral, for improving wet traction of tires (abs-S98#19) (4) 824
- Filled rubber, role of filler networking in dynamic properties (abs-S98#48) (4) 831
- Filler, for rubber compounding, from scrap rubber powder (5) 1028
- Filler-filler and filler-polymer interactions, in rubber-carbon black dispersions (abs-S98#57) (4) 833
- Filler-filler interactions, effect on dynamic properties of filled vulcanizates (rev) (3) 520
- Fillers, black and white, for tires (rev) (3) 323
- Fillers, carbon-silica dual phase, estimating functional groups on surface of (5) 1015
- Finite element method (FEM), in design of automotive weather strips, model for compressibility (abs-S98#49) (4) 831
- Flame retardants, in rate water-cured polyethylene cable jacket (abs-S98#31) (4) 827
- Flex cracking, of blends of brominated isobutylene *p*-methylstyrene copolymer/diene elastomers (abs-S98#24) (4) 825
- Fluid dynamics analysis package, for analyzing flow patterns in distributive mixing (4) 690
- Fluorinated di-olefin, curing agent for perfluoroelastomers for high temperature applications (abs-S98#16) (4) 823
- Fluoroelastomer scrap, recycling in presence of specially formulated Carrier Gum (abs-F97#115) (1) 151
- Fluoroelastomer, based on bisphenol AF/osmium cure system, storage stability, use as reference (abs-F97#26) (1) 126
- Fluoroelastomers, adhesion to metal using water-soluble polymer coupling agents (abs-S98#70) (4) 836
- Fluoroelastomers, peroxide cured, with expanded fluid resistance (abs-F97#32) (1) 128
- Foamed profiles, of Santoprene<sup>®</sup>, using water as blowing agent (abs-S98#51) (4) 832
- Foams, high density, correlation of compressibility and stiffness (abs-F97#55) (1) 135
- Fractal nature of carbon black, as related to dynamic behavior of elastomers at low strain amplitudes (abs-S98#56) (4) 833
- Fracture energy calculation, in crack growth of twisted rubber disks (1) 76
- Fracture mechanics, application to failure of rubber-cord laminates (abs-F97#34) (1) 128
- Gamma-radiation, for optimizing properties of PDMS elastomers with blended silica fillers (5) 928
- Geometry of sample, and effect on properties of cord-rubber composite (abs-F97#10) (1) 121
- Glass and carbon fibers, in polyurethane composites, viscoelastic characterization (5) 1042
- Goodyear Medal Address, 1998 (rev) (3) 323
- Ground rubber particles, in vulcanized SBR, effect on tensile behavior (5) 861
- Ground scrap, additives for enhancing properties for use in new tires (abs-F97#81) (1) 142
- Ground scrap, used in coolant hose, brake cups and floor mat backing (abs-F97#80) (1) 141
- HIPS, with high gloss and core shell structure, using SB-block copolymer (abs-F97#14) (1) 122

- HNBR elastomers, crosslinking by sulfur versus peroxide (abs-S98#13) (4) 823
- HNBR, analytical studies of exposure to automotive lubricants for long term serviceability (abs-F97#123) (1) 153
- HNBR, compression set (abs-F97#125) (1) 154
- HNBR, for engine mounts, laboratory testing for relevant properties (abs-F97#42) (1) 131
- HNBR, structure property relations after exposure to automotive transmission fluids (abs-F97#124) (1) 154
- HNBR/ZMA composite, for heavy load and heat resistance in roll applications (abs-F97#122) (1) 153
- HTS [1,6-hexamethylene bis(sodium thiosulfate)], vulcanizing agent for BIMS, studied by XANES (abs-S98#10) (4) 822
- HTS [hexamethylene-1,6-bis-(thiosulfate)], for reversion resistance of diene rubbers (abs-F97#107) (1) 149
- Halobutyl rubbers, ozone-resistant, for black sidewalls (rev) (3) 590
- Hardness testing, reducing time of with IRHD (abs-F97#4) (1) 119
- Heat aging, of EPDM in electrical insulation, effect of antioxidants on (abs-S98#27) (4) 826
- Heating and cooling rates, effect on carbon black structure (1) 26
- High-resistivity measurement of rubber, repeatable, using alternating polarity (abs-F97#33) (1) 128
- Hose, of knitted *para*-aramid fiber, influence of yarn properties on hose performance (abs-F97#50) (1) 134
- Hysteresis and modulus, of polymer systems, related to filler networking (abs-S98#48) (4) 831
- Hysteresis, in carbon black-filled rubbers containing tin end-modified polymers (4) 637
- IR, sulfur vulcanized, accelerated by 2-*t*-butylbenzothiazole sulfenamide (abs-S98#12) (4) 822
- IRHD, International Rubber Hardness Degree, method for non-destructive testing of rubbers (abs-F97#4) (1) 119
- Impact modifier, for HIPS, using SB-block copolymer (abs-F97#14) (1) 122
- Injection molding, of NR, simulation and experimental studies (abs-F97#78) (1) 141
- Injection molding, of NR, simulation and experimental studies (5) 1059
- Injection molding, of elastomers, mold design and rheological factors involved (abs-F97#77) (1) 140
- Injection molding, of glass-filled polyurethane (abs-S98#59) (4) 834
- Injection molding, of rubber, extruder design press parameter settings (abs-F97#76) (1) 140
- Insulation, electrical, EPDM polymers for (abs-S98#35) (4) 828
- Intermix technology, new developments (abs-F97#101) (1) 147
- Internal mixing, managing on-line with PLC (abs-S98#66) (4) 835
- Isobutylene-based elastomers, solid-state NMR study of differential curing (abs-F97#70) (1) 139
- Isobutylene-based graft copolymers, characterization and physical properties of (4) 803
- Isoprene, alkyl tetrahydrofurfuryl ether modifiers for anionic polymerization (1) 62
- Kinetics, non-isothermal, of formation of durable bonds in molding (abs-F97#22) (1) 124
- LR 3024 SERIES, liquid silicone rubbers for oil sealing applications with no post cure (abs-F97#30) (1) 127
- Laminated composites, two-dimensional constitutive equation for studying (abs-F97#12) (1) 121
- Laser scanning, line, of tires and extrusions (abs-F97#1) (1) 119
- Laser-optic triangulation, for measuring inside and outside diameter of rubber hose (abs-F97#120) (1) 153
- Lead stabilizers, of low extractability, for use with EPDM, CPE, CSM, ECO and FKM elastomers (abs-S98#36) (4) 828
- MR-VK, recycled rubber blended with virgin polyisoprene, in various formulations (abs-F97#27) (1) 126
- Maleinized polybutadiene resins, for promoting adhesion of dissimilar rubbers (abs-F97#20) (1) 124
- Mathematical equations, combined with computers for studying chemical systems (abs-F97#56) (1) 135
- Mathematical model, of diffusion of solvents in rubbers (2) 285
- Mathematical modeling, for understanding cord-rubber composites (abs-F97#9) (1) 121
- Matrix viscosity and interfacial properties, influence on carbon black dispersion (1) 1
- Mechanical and dielectric properties, of carbon black, correlations between (abs-S98#47) (4) 831
- Mechanical deformation, of cord-rubber composites, reviewed (abs-F97#9) (1) 121
- Mechanical fatigue wear, of elastomers, simulating surface flaw propagation in (abs-S98#22) (4) 824



- Mechanical fatigue wear, of elastomers, surface flaw propagation associated with (2) 214
- Mechanical properties, of PDMS elastomers correlated with swelling and structure (5) 941
- Mechanochemical recovery, of rubber from scrap tires (abs-F97#117) (1) 152
- Melamine resins, in new wire adhesion system (abs-F97#21) (1) 124
- Melt mixing, of polypropylene elastomers, semicrystalline plastics and blends (2) 244
- Mercury porosimetry, for determining primary particle size of carbon black in aggregates (5) 988
- Metallic stearates, release agents for rubber compounds (abs-S98#45) (4) 830
- Metallocene EPDM, new class through constrained geometry catalyst technology (abs-F97#44) (1) 132
- Microimaging, Raman, in characterization of polymers (abs-S98#7) (4) 821
- Microscopic image analysis, of elastomers to infer physical properties (abs-S98#23) (4) 825
- Microscopy, of unvulcanized blends of NR/HDPE (5) 966
- Mineral oil, effect of properties of polyolefin elastomers (abs-F97#19) (1) 124
- Mixers, intensive internal batch, feeding and weighing systems for (abs-F97#86) (1) 142
- Mixers, intermeshing, technology (abs-F97#101) (1) 147
- Mixers, internal, advanced technology (abs-F97#58) (1) 136
- Mixers, internal, advanced technology (abs-F97#88) (1) 143
- Mixers, internal, with HDM (high distributive mixing) tangential rotors (abs-F97#89) (1) 143
- Mixers, variable intermeshing clearance, simulation of distributive mixing (4) 690
- Mixers, with variable intermeshing clearance, for distributive mixing (abs-F97#116) (1) 151
- Mixing mechanism, in rubber, understanding from scientific viewpoint (abs-F97#60) (1) 136
- Mixing quality, of silica in NR, checked through FTIR (2) 300
- Mixing rooms, for tire manufacture (abs-F97#85) (1) 142
- Mixing temperature, effect of nitrosamine formation in vulcanization (2) 310
- Mixing, extrusion, and injection molding of rubber (abs-F97#357) (1) 135
- Mixing, of rubber, materials problems (abs-F97#59) (1) 136
- Mixing, optimizing performance through filler dispersion control (abs-F97#102) (1) 147
- Mixing, summary of tests for optimizing (abs-F97#100) (1) 147
- Model, for compressible elastic behavior of sponge rubber, with FEM (abs-S98#49) (4) 831
- Model, for studying deformation of elastomer laminates (abs-F97#12) (1) 121
- Modeling, non-linear viscoelastic, of highly filled crosslinked systems (abs-S98#21) (4) 824
- Modeling, of elastomers, structurally realistic (rev) (3) 342
- Modeling, of incompressible elastomers, during non-homogeneous deformations (4) 730
- Modeling, of peroxide cured HNBR compounds for seal applications (abs-S98#14) (4) 823
- Modulus, apparent, of porous bonded blocks (abs-F97#55) (1) 135
- Mold design, as consideration in effective injection molding of elastomers (abs-F97#77) (1) 140
- Mold release agents, water-based, performance review of (abs-S98#43) (4) 830
- Molding temperature, importance in formation of durable bonds (abs-F97#22) (1) 124
- Molecular dynamics and bulk simulations, for modeling elastomers (rev) (3) 342
- Mooney viscometer with stress relaxation, for processability measures of NBR (abs-F97#90) (1) 144
- Morphology, three-dimensional, of carbon black aggregates (abs-S98#46) (4) 831
- Mullin's effect, studied in tire tread and sidewall compounds (abs-F97#93) (1) 144
- N*-(1,3-dimethylbutyl)-*N'*-phenyl quinone diimine, antioxidant/inhibitor for rubber industry (abs-F97#109) (1) 149
- N*-nitrosamines, detection in baby bottle nipples (abs-F97#130) (1) 155
- NBR, processibility measurements using Rubber Process Analyzer and Mooney viscometer (abs-F97#90) (1) 144
- NBR, properties of compound using re-utilized factory scrap (abs-F97#98) (1) 146
- NBR, reinforcement with silica generated *in situ* (1) 38
- NMR, of tissues exposed to polysiloxane gels (1) 95
- NMR, solid-state, for studying differential curing of isobutylene-based elastomers (abs-F97#70) (1) 139
- NR latex, vulcanized by radiation (abs-F97#31) (1) 127
- NR vulcanizates, unfilled, continuous ultrasonic devulcanization (abs-F97#83) (1) 142
- NR, adhesion to steel with plasma polymerized primers (abs-F97#49) (1) 133
- NR, black-filled, tensile and tear behavior of anisotropic double networks (abs-S98#60A) (4) 834
- NR, black-filled, tensile and tear behavior of anisotropic double networks (5) 846

- NR, carbon black filled, formation of longitudinal cracks during chemical relaxation (abs-F97#53) (1) 134
- NR, crystallization and strength compared to that of synthetic *cis*-1,4-polyisoprene (4) 668
- NR, effect of fatty acids on crystallization (1) 70
- NR, lamellar crystal grown from dilute solution, finding stem length of (2) 277
- NR, low molecular weight telechelic latex preparation (4) 795
- NR, silica-filled, FTIR analysis (2) 300
- NR, simulation and experimental studies of injection molding (5) 1059
- NR/BR blends, crosslink density distribution, effect of cure temperature and time (5) 958
- NR/BR blends, effect of cure temperature on crosslink density distribution (abs-F97#94) (1) 145
- NR/cardinol-formaldehyde resin blends, for improved thermal and mechanical properties (abs-S98#58) (4) 834
- Network analysis, of NR crosslinked with bis-maleimide or bis-citraconimide (5) 1073
- Neutron scattering, for studying carbon black shape and surface structure (abs-S98#41) (4) 829
- Nitrile rubbers, for automotive applications (rev) (3) 440
- Nitrosamine formation in vulcanizates, influence of mixing temperature (2) 310
- Nitrosamine formation, in EPDM rubber, influence of cure (4) 766
- Non-contact magnetostrictive linear sensors, for use in rubber molding (abs-S98#68) (4) 835
- Non-linear dynamic mechanical responses, in filled crosslinked rubbers (abs-S98#21) (4) 824
- Oil sealing applications, of liquid silicone rubbers needing no post cure (abs-F97#30) (1) 127
- Oxidation, of elastomers, studied by DSC (abs-S98#11) (4) 822
- Ozone cracking, blends of brominated isobutylene *p*-methylstyrene copolymer/diene elastomers (abs-S98#24) (4) 825
- PDMS (poly[dimethylsiloxane] elastomers), mechanical properties (5) 941
- PDMS (poly[dimethylsiloxane] elastomers), preparation, curing and aging processes (5) 906
- Particle size distribution, in carbon black aggregates, by mercury porosimetry (5) 988
- Paving, asphalt, modified by tire scrap, performance of (abs-F97#95) (1) 145
- Perfluoroelastomers, for high temperature applications, cured by peroxides (abs-S98#16) (4) 823
- Peroxide cure, for HNBR in seal applications (abs-S98#14) (4) 823
- Peroxide cure, of perfluoroelastomers for high temperature applications (abs-S98#16) (4) 823
- Peroxide curing, of NR containing precipitated silica (abs-S98#17) (4) 823
- Peroxide curing, of millable polyurethane rubber (abs-S98#15) (4) 823
- Peroxide vulcanization, of elastomers (abs-S98#6) (4) 821
- Peroxide-cured elastomers, coagent selection (abs-S98#4) (4) 821
- Peroxides, mechanism of crosslinking polymers with (abs-S98#1) (4) 820
- Peroxides, organic, for crosslinking of polyolefins (abs-S98#3) (4) 820
- Peroxides, organic, for crosslinking polymers (abs-S98#2) (4) 820
- Phase morphology, of blends of unvulcanized NR/HDPE, use of quick-quenched samples (5) 966
- Plasma polymerized primers, for adhesion of NR to steel (abs-F97#49) (1) 133
- Plasticization of polyolefin elastomers and semicrystalline plastics during melt mixing (2) 244
- Plasticizers and fillers, effect on formulated EPDM made using constrained geometry catalyst (abs-F97#45) (1) 132
- Polarity, of carbon black surface as it affects compatibility with EPDM (abs-F97#43) (1) 131
- Poly(dimethylsiloxane) elastomers, from aqueous emulsions, role of silane crosslinker (abs-F97#128) (1) 154
- Poly(styrene-*b*-isobutylene arms on core of calix[8]arene; for superior properties (abs-F97#18) (1) 123
- Polyacrylic elastomers, for automotive applications (rev) (3) 440
- Polychloroprene compounds, change in dynamic properties with long term aging (abs-F97#54) (1) 135
- Polydivinylbenzene, star block copolymers with multiple polystyrene/polyisobutylene-based arms (5) 949
- Polyisobutylene block copolymer, with polystyrene or poly-*t*-butylstyrene end blocks (abs-F97#17) (1) 123
- Polyisoprene rubber, effect of silica as filler (abs-F97#69) (1) 138
- Polyisoprene, dispersed in SBR, crystallization (5) 837
- Polymer dispersion, control in mixing procedure to improve crack growth resistance (abs-F97#65) (1) 138
- Polymer-filler interactions, effect on dynamic properties of filled vulcanizates (rev) (3) 520



- Polyolefin elastomers, effect of white mineral oil and hydrocarbon process oils on properties (abs-F97#19) (1) 124
- Polyolefins, crosslinking by organic peroxides (abs-S98#3) (4) 820
- Polypropylene elastomers, plasticization and crosslinking *in situ* during melt blending (2) 244
- Polysiloxane gels, for breast implants, migration and modification in the body (1) 95
- Polyurethane composites, filament wound with high fiber, viscoelastic properties (5) 1042
- Polyurethane compound, filament-wound high fiber, viscoelastic characteristics of matrix (abs-F97#13) (1) 122
- Polyurethane rubber, millable, peroxide curing of (abs-S98#15) (4) 823
- Polyurethane rubber, millable, with versatile functions (abs-F97#8) (1) 121
- Polyurethane, glass-filled, rheology, injection molding, and properties of (abs-S98#59) (4) 834
- Power transmission belt, performance and failure (rev) (3) 619
- Power transmission belting, performance and failure studies (abs-F97#47) (1) 133
- Pre-dispersion, of silica in emulsion polymers (abs-F97#127) (1) 154
- Programmable Logical Controller (PLC), for managing internal mixing on-line (abs-S98#66) (4) 835
- Protac NPT, non-phenolic tackifier (abs-F97#29) (1) 127
- Pyro-char, from scrap tires, used in asphalt pavements (abs-F97#115A) (1) 151
- Pyrolysis GC/MS, for determining amounts of SBR, NBR and PBD in compounded stocks (abs-F97#72) (1) 139
- Quality control, in tire manufacturing, through real time shearography (abs-F97#118) (1) 152
- Radiation vulcanized NR latex (abs-F97#31) (1) 127
- Ram position indicator, for controlling batch mixing (abs-F97#87) (1) 143
- Raman microimaging, in characterization of polymers (abs-S98#7) (4) 821
- Raman spectra, high pressure, for studying particles of graphite and carbon blacks (abs-S98#39) (4) 829
- Reaction stage modeling, after cross link formation, to study role of zinc(II) catalyst (4) 750
- Recycled rubber, post-consumer evaluation (abs-F97#80) (1) 141
- Recycling rubber, by devulcanizing (abs-F97#97) (1) 146
- Reflectometry, for measuring carbon black dispersion (1) 17
- Reinforcement, of NBR, by silica generated *in situ* (1) 38
- Release agents, for rubber compounds, using meallic stearates as (abs-S98#45) (4) 830
- Release agents, for tire molding (abs-S98#44) (4) 830
- Reproducing Kernel Particle Method, for large deformation contact analysis of elastomers (2) 168
- Retarder/kicker, for SBR and NR, at various temperatures and with silica (abs-F97#108) (1) 149
- Retarding properties, of Vulkalant E sulfonamide derivative (abs-F97#28) (1) 126
- Reversion resistance, in thick-section molded NR, by using dithiophosphate (abs-F97#106) (1) 148
- Reversion resistance, of sulfur vulcanized diene rubbers, by BCL-MX and HTS (abs-F97#107) (1) 149
- Rheological behavior, of glass-filled polyurethane (abs-S98#59) (4) 834
- Rheological behavior, of graft copolymers based on isobutylene terpolymers (4) 803
- Rheological factors, as consideration in effective injection molding of elastomers (abs-F97#77) (1) 140
- Rheology, and relation to mixing performance of gum rubber (abs-F97#60) (1) 136
- Rheology, of rubber (abs-F97#357) (1) 135
- Rim flange abrasion, as indicator of over-deflected operating conditions in tires (abs-F97#51) (1) 134
- Rollers, for steel and paper lines, HNBR/ZMA composites for load and heat resistance in (abs-F97#122) (1) 153
- Rotational isomeric state methods, of modeling elastomers (rev) (3) 342
- Rubber Division, ACS, Charles Goodyear Medalist—1998, Jean-Baptiste Donnet (3) G39
- Rubber Division, ACS, Program for 1998 Fall Meeting (5) G32
- Rubber Process Analyzer, for measuring processibility of NBR (abs-F97#90) (1) 144
- Rubber hose, measuring inside and outside diameter using laser-optic triangulation (abs-F97#120) (1) 153
- Rubber molding, using non-contact magnetostrictive linear sensors (abs-S98#68) (4) 835
- Rubber processing, introduction to science of (abs-F97#357) (1) 135
- Rubber processing, overview of symposium (abs-F97#79) (1) 141
- Rubber-cord laminates, application of fracture mechanics to failure (abs-F97#34) (1) 128
- Rubber-glass transitions, as related to wet skid properties (1) 53

- Rubber-metal bonding studies, using designed experiments (abs-F97#25) (1) 125
- Rubber-to-metal adhesion test, double-peel method (abs-F97#24) (1) 125
- Rubber-to-metal adhesives, aqueous, application characteristics (abs-F97#23) (1) 125
- Rubber/plastic blends, based on devulcanized ground tire rubber (abs-F97#114) (1) 151
- Rubberlike elasticity, studied with Valanis-Landel form of stored energy function (2) 234
- SAXS, for studying carbon black surface (abs-S98#40) (4) 829
- SB-block copolymer, as modifier for HIPS with high gloss and core-shell structure (abs-F97#14) (1) 122
- SBR rubber, effect of bis(3-triethoxysilylpropyl)tetrasulfide on silica reinforcement (2) 289
- SBR vulcanizate, effect of ground rubber particles on tensile behavior (5) 861
- SBR, NBR, and PBD, determining amounts in compounded stocks by pyrolysis GC/MS (abs-F97#72) (1) 139
- SBR, blends with NR, crystallization studies of (5) 861
- SBR, blends with devulcanized silicone rubber, surface behavior (abs-F97#113) (1) 150
- SBR, properties of compound using re-utilized factory scrap (abs-F97#98) (1) 146
- SBR, sulfur cured, effect of carbon black on ultrasound devulcanization (abs-F97#99) (1) 146
- SBR, ultrasonic devulcanization, modeling based on cavitation and percolation theories (2) 168
- Scanning probe microscopy, for studying carbon black surface (abs-S98#40) (4) 829
- Scrap rubber, blended with virgin polyisoprene, for materials with tailored properties (abs-F97#27) (1) 126
- Scrap rubber, recovered by high shear and high temperature pyrolysis (abs-F97#98) (1) 146
- Scrap tires, cryogenic grinding to fine mesh crumb (abs-F97#111) (1) 150
- Scrap tires, mechanochemical recovery of rubber from (abs-F97#117) (1) 152
- Scrap tires, pyrolyzed to char and used in asphalt pavement (abs-F97#115A) (1) 151
- Scrap tires, utilized as crumb for filler in rubber compounding (5) 1028
- Seal, for high temperature use, from peroxide cured perfluoroelastomers (abs-S98#16) (4) 823
- Seals, automotive, long term serviceability of HNBR elastomers for (abs-F97#123) (1) 153
- Seals, of peroxide cured HNBR (abs-S98#14) (4) 823
- Seals, of sulfur-cured EPDM made by constrained geometry catalyst (abs-S98#52) (4) 832
- Serviceability, of HNBR parts in automotive lubricants, long term (abs-F97#124) (1) 154
- Shearography, real time, for tire manufacturing process control (abs-F97#118) (1) 152
- Silane crosslinker concentration, relation to properties of PDMS (5) 941
- Silane, grafted onto polyolefins, for cross-linkable cable insulation (abs-S98#28) (4) 826
- Silica fillers, blended into PDMS elastomer, resulting in elastomer dispersed in silica phase (5) 928
- Silica reinforcement, of SBR, effect of bis(3-triethoxysilylpropyl)tetrasulfide on (2) 289
- Silica wet masterbatch, for pre-dispersion of silica in emulsion polymers (abs-F97#127) (1) 154
- Silica, effect on vulcanization chemistry of NR (abs-F97#69) (1) 138
- Silica, generated *in situ*, for reinforcing NBR (1) 38
- Silica, in NR, FTIR check for levels (2) 300
- Silica, incorporated into matrix of carbon-silica dual phase filler (abs-S98#9) (4) 822
- Silica-reinforced NR, peroxide cure for (abs-S98#17) (4) 823
- Silicone rubber, for tire curing bladders, coating system for (abs-S98#42) (4) 830
- Silicone rubber, unfilled, continuous ultrasonic devulcanization (abs-F97#96) (1) 145
- Silicone rubbers, liquid, for oil sealing applications needing no post cure (abs-F97#30) (1) 127
- Single chain simulations, in modeling elastomers (rev) (3) 342
- Solvents, mathematical model of diffusion in rubbers (2) 285
- Specialty elastomers, for automotive applications (rev) (3) 440
- Sponge formulation, of EPDM, optimum characteristics for continuous vulcanization (abs-S98#50) (4) 832
- Sponge rubber, cell density and structure controlled by balancing cure and blow reactions (abs-S98#53) (4) 833
- Star block copolymer, based on calix[8]arene core with poly(styrene-*b*-isobutylene) arms (abs-F97#18) (1) 123
- Star-block TPE, with multiple polystyrene-*b*-polybutylene arms radiating from polydivinylbenzene (5) 949
- Star-block TPEs, with superior tensile and lower melt viscosities (abs-F97#16) (1) 123
- Star-block polymers, with 8 poly(styrene-*b*-isobutylene) arms and calix [8]arene core (4) 708

- Stem length, of chain-folded lamellar crystal grown from dilute solution of NR (2) 277
- Storage, effect on properties of polychloroprene formulations (abs-F97#54) (1) 135
- Stored energy function, in molecular theory of elasticity (2) 234
- Stress relaxation, chemical, of carbon black filled NR giving longitudinal cracks (2) 157
- Stress-relaxation, non-linear, in filled and crosslinked rubbers (abs-F97#93) (1) 144
- Strip handling, new machinery (abs-F97104A) (1) 148
- Sulfur cured EPDM, using low nitrosamine accelerator, for sealing applications (abs-S98#52) (4) 832
- Surface behavior, of blends of SBR with ultrasonically devulcanized silicone rubber (abs-F97#113) (1) 150
- Surface chemistry study, of carbon-silica dual phase filler, to find reactive functional group (abs-F97#73) (1) 139
- Surface flaw propagation, in mechanical fatigue of elastomers, simulation of (abs-S98#22) (4) 824
- Surface flaw propagation, in mechanical fatigue wear, of elastomers (2) 214
- Surface, of carbon black, detecting foreign elements on by ToF-SIMS and XPS (abs-S98#38) (4) 828
- Swell ratio, for studying covulcanizates of BR, NR and poly(isobutylene-co-paramethylstyrene) (abs-F97#91) (1) 144
- TCLP (Toxic Characteristic Leaching Procedure) for detecting lead-containing additives in scrap (abs-S98#36) (4) 828
- TPE, star-block, with polystyrene-*b*-polyisobutylene arms, for superior tensile (abs-F97#16) (1) 123
- TPO, high flow, modified with branched EPDM compound for better impact resistance (4) 778
- TPO, high flow, modified with branched EPDM compounds for better impact resistance (abs-F97#15) (1) 122
- TSR—Twin screw roller die (abs-F97#2) (1) 119
- Tackifier, non-phenolic (abs-F97#29) (1) 127
- Tangential rotor design, for internal mixers (abs-F97#89) (1) 143
- Tear energy, calculating from viscoelastic behavior of elastomers (4) 679
- Tear strength, of double networks of black-filled NR vulcanizate (5) 846
- Tensile and tear behavior, of anisotropic double networks of black-filled NR vulcanizates (abs-S98#60A) (4) 834
- Tensile behavior, of SBR, as affected by presence of ground rubber particles (5) 861
- Tensile strength, of double networks of black-filled NR vulcanizates (5) 846
- Testing methodology, of reinforced rubber matrix composites (abs-F97#46) (1) 132
- Tetraisobutylthiuram monosulfide: retarder/kicker for SBR and NR at various cure temperatures (abs-F97#108) (1) 149
- Textile-to-rubber bonding agent, from shorea robusta resin (abs-F97#7) (1) 120
- Textile-to-rubber bonding agent, from shorea robusta resin (abs-F97#7) (1) 120
- The role of filler networking in dynamic properties of filled rubber (abs-S98#48) (4) 831
- Thermoplastic vulcanizates, with improved wet electrical properties (abs-S98#32) (4) 827
- TiBTM (Tetraisobutylthiuram monosulfide), retarder/kicker for SBR and NR (abs-F97#108) (1) 149
- Time-temperature superposition of dynamic properties, of carbon-silica filled vulcanizates (abs-S98#20) (4) 824
- Tire black sidewall, surface discoloration and non-staining technology (rev) (3) 590
- Tire component, state-of-the-art extrusion (abs-F973104) (1) 148
- Tire curing bladders, of silicone rubber, coating systems for (abs-S98#42) (4) 830
- Tire manufacture, using made-to-measure mixing rooms (abs-F97#85) (1) 142
- Tire manufacturing, real time shearography for real time process control in (abs-F97#118) (1) 152
- Tire materials, effect of polymer-filler and filler-filler interactions on dynamic properties (rev) (3) 520
- Tire mechanics analysis, checking validity of finite element models (abs-F97#48) (1) 133
- Tire performance, as related to improved dispersion of carbon black filler (abs-S98#57) (4) 833
- Tire recycling, using resulting crumb as filler in rubber compounding (5) 1028
- Tire scrap, as modifiers for asphalt paving, performance of (abs-F97#95) (1) 145
- Tire scrap, ground, devulcanized and blended with PP (abs-F97#114) (1) 151
- Tire sidewall appearance, assessing crack growth resistance with highly saturated polymers (abs-F97#65) (1) 138
- Tire sidewall appearance, improving by dispersion control in mixing (abs-F97#65) (1) 138
- Tire sidewalls, non-stain, using new grades of BIMS (abs-F97#66) (1) 138

- Tire tread and sidewall recipes, testing nonlinear dynamic mechanical response (abs-S98#21) (4) 824
- Tire tread, computer-controlled evaluation of traction and wear (abs-F97#119) (1) 152
- Tires, aircraft, studying fatigue in cord-rubber composites for (5) 889
- Tires, aircraft, studying fatigue of cord-rubber composites in (5) 866
- Tires, bias and radial, deformation testing (abs-F97#48) (1) 133
- Tires, black and white fillers (rev) (3) 323
- Tires, black sidewall, using triazine and octylated diphenylamine (abs-F97#64) (1) 137
- Tires, detecting over-deflected operating conditions through compression grooving (abs-F97#51) (1) 134
- Tires, line laser scanning of (abs-F97#1) (1) 119
- Tires, using treated ground scrap (abs-F97#81) (1) 142
- Tires, wet traction improved by mineral fillers (abs-S98#19) (4) 824
- ToF-SIMS, for characterizing surface of carbon black (abs-S98#38) (4) 828
- Torsion test, for determining crack growth (1) 84
- Transmission seals, analysis by atomic force microscopy (abs-F97#67) (1) 138
- Tread and sidewall formulations, studied by non-linear stress relaxation (abs-F97#93) (1) 144
- Twaron<sup>®</sup> para-aramid fiber, in hose; influence of yarn properties on hose performance (abs-F97#50) (1) 134
- Twaron<sup>®</sup>, p-aramid fiber for mechanical goods (abs-F97#6) (1) 120
- Ultrasonic devulcanization, of SBR rubber, modeling based on cavitation and percolation theory (2) 168
- Ultrasonic devulcanization, of unfilled NR vulcanizates (abs-F97#83) (1) 142
- Ultrasound devulcanization, of sulfur cured SBR, effect of carbon black (abs-F97#99) (1) 146
- Valanis-Landel form, of stored energy function, in molecular theories of rubber elasticity (2) 234
- Vehicle Recycling Partnership, program for using ground automotive scrap for hose, brake cups (abs-F97#80) (1) 141
- Vinyl elastomers, in large, non-homogeneous deformation states, modeling (4) 730
- Vinyl norbornene, as monomer in special EPDM for wire and cable use (abs-S98#29) (4) 827
- Vinyl norbornene, in special EPDM for wire and cable insulation (abs-F97#41) (1) 131
- Viscoelastic behavior, of EPDM, influence of molecular structure (abs-F97#44) (1) 132
- Viscoelastic behavior, of elastomers, for calculating tear energy (4) 679
- Viscoelasticity, of filament-wound polyurethane matrix composite with high fiber content (abs-F97#13) (1) 122
- Viton<sup>®</sup> ETP, fluoroelastomer with expanded fluids resistance (abs-F97#32) (1) 128
- Vulkalent E, sulfonamide derivative, retarder and accelerator of vulcanization (abs-F97#28) (1) 126
- Water, as blowing agent for thermoplastic elastomer foams (abs-S98#51) (4) 832
- Wet aging, of poly(dimethylsiloxane) elastomers (abs-F97#128) (1) 154
- Wet skid properties, of filled rubbers (1) 53
- Wire adhesion, present and future (abs-F97#21) (1) 124
- Wire and cable applications, of EPDM made with vinyl norbornene (abs-S98#29) (4) 827
- Wire and cable applications, of thermoplastic vulcanizates (abs-S98#32) (4) 827
- Wire and cable insulation, using advanced EPDM compounds (abs-F97#41) (1) 131
- Wire and cable, automotive, recent advances (abs-S98#32) (4) 827
- Wire and cable, elastomers in (abs-S98#26) (4) 826
- Wire and cable, new metal clad aramid fibers for use with (abs-S98#37) (4) 828
- Wire reinforced rubber, effects of material and loading on fatigue crack growth (abs-F97#35) (1) 128
- XANES, X-ray absorption near edge structures spectroscopy, for studying HTR curing of BIMS (abs-S98#10) (4) 822
- XPS, for characterizing surface of carbon black (abs-S98#38) (4) 828
- Zimbabwe, state of the rubber industry (abs-S98#71) (4) 836
- Zinc(II) catalysis, in accelerated vulcanization, studied by reaction stage modeling (4) 750
- Bis(dimethylthiocarbamate)zinc(II), catalyst for disproportionation in vulcanization (4) 750
- p-Phenylenediamine-type antiozonants, protection mechanism of (4) 722

